


Internal & External Skive Swage Ferrule for Spiral Hose Series 15037

ecoVOS⁺

B



Ferrule Type with Pull-Out Protection (Interlock)

Suitable for 4SP, 4SH,
R15 (DN 19 / DN 25)

Standards EN 856, SAE 100 R15


Material Carbon Steel

Surface Finishing Zinc/Nickel-Plating $\Delta plus$

Maximum working pressures depending on the type of the hose connector and the hose type.

Hose Size			Dimensions (mm/in)					Weight (^{kg/lbs}) ca. per 100	VOSWINKEL Part Numbers	STAUFF Ordering Codes
DN	inch	Dash	D	D1	D2	L	b			
16	5/8"	-10	22,6	27	33,6	40,0	2,5	7,55	15037N16	HF-5002-16-W3
			,89	1,06	1,32	1,57	,10	16,65		
19	3/4"	-12	25,5	30,2	39,0	50,0	3,0	15,5	15037N20	HF-5002-19-W3
			1,00	1,19	1,54	1,97	,12	34,18		
25	1"	-16	31,0	36,7	46,0	60,0	3,7	22,9	15037N25	HF-5002-25-W3
			1,22	1,44	1,81	2,36	,15	50,49		
31	1 1/4"	-20	39,2	47,0	57,0	65,0	4,0	34,1	15037N32	HF-5002-31-W3
			1,54	1,85	2,24	2,56	,16	75,19		
38	1 1/2"	-24	45,0	53,7	65,0	73,0	4,3	52,1	15037N40	HF-5002-38-W3
			1,77	2,11	2,56	2,87	,17	114,88		
51	2"	-32	58,5	66,0	78,0	80,0	4,3	70,2	15037N50	HF-5002-51-W3
			2,30	2,60	3,07	3,15	,17	154,79		

Mobile Interlocking Protection Ring Type AS



Hose Size			Dimensions (mm/in)						Weight (^{kg/lbs}) ca. per 100	VOSWINKEL Part Numbers	STAUFF Ordering Codes
DN	inch	Dash	D	D1	D2	D3	L	L1			
16	5/8"	-10	20,0	16,8	15,3	19,5	7,5	5,0	5,5	10037K16	HCE-AS-16-PEK
			,79	,66	,60	,77	,30	,20	12,13		
19	3/4"	-12	24,0	20,1	18,5	22,5	9,5	5,9	9,6	10037K20	HCE-AS-19-PEK
			,94	,79	,73	,89	,37	,23	21,17		
25	1"	-16	30,0	26,7	25,2	29,1	9,5	5,9	11,9	10037K25	HCE-AS-25-PEK
			1,18	1,05	,99	1,15	,37	,23	26,24		
31	1 1/4"	-20	37,5	33,4	31,8	36,1	11,5	7,8	20,2	10037K32	HCE-AS-31-PEK
			1,48	1,31	1,25	1,42	,45	,31	44,54		
38	1 1/2"	-24	43,8	39,5	37,9	42,4	15,5	10,8	33,8	10037K40	HCE-AS-38-PEK
			1,72	1,56	1,49	1,67	,61	,43	74,53		
51	2"	-32	56,0	53,1	50,6	52,6	15,5	10,8	51,0	10037K50	HCE-AS-51-PEK
			2,20	2,09	1,99	2,07	,61	,43	112,46		

